



PATIL DYESTUFF INDUSTRIES
Skycat Clean - For sure

TECHNICAL DATA SHEET

SKYCAT PT 40

SKYCAT PT 40 is a titanium complex of ethyl acetoacetate with Alkyl silane. **SKYCAT PT 40** is used in a variety of industrial applications e.g. as an adhesion promoter, as a crosslinking agent for hydroxylic compounds and as a cure catalyst for neutral cure RTV silicone sealants. **SKYCAT PT 40** is also useful as a binder and also can be used as an adhesion promoter or cross-linking agent for –OH, or –COOH functional polymer and paints.

Physical and Chemical Properties

Sr. No.	Parameter	Test Method	Typical Value
1	Appearance	Visual	Yellow to amber clear Liquid
2	K. Viscosity @ 20 deg C, cSt	ASTM D-445	10 - 15
3	Specific Gravity @ 20 deg C	ASTM D-891	1.080 – 1.100
4	Flash Point deg C	ASTM D-93	36
5	Ti Content %	ITM/QC/07	9.00 – 9.60
6	CAS No.	-----	27858-32-8

PACKAGING

Type	ISO Tanker	IBC	M.S. Barrels
SKYCAT PT 40	As per Customer Requirement	1000 Kgs	200 Kgs

The information in this publication is provided in good faith and is believed to be accurate. However, customers should determine the suitability of the product for their specific needs. Patil Dyestuff Industries makes no guarantees regarding the product's fitness for any particular purpose, and any implied warranties or conditions (statutory or otherwise) are disclaimed to the fullest extent permitted by law.

Patil Dyestuff Industries
C-1, B- 67/605, 100 Shed Area, GIDC, Vapi - 396195, Valsad, Gujarat, India
Tel. No. : +91 - 9998926100, +91 82389 66188 URL : www.patildyestuff.com